

Technical data

Art. no.	10887
Gauge	H0e / TT / N
PIN/Interface	6 pole, angled pins
According to NEM	☒ Yes ☐ No 651
Cable	☐ Yes ☒ No
DCC	☒ Yes ☐ No
MM	☒ Yes ☐ No
Load regulation	☒ Yes ☐ No
POM	☒ Yes ☐ No
NMRA compatible	☒ Yes ☐ No
Speed steps (14, 28, 128)	☒ Yes ☐ No
Max. motor current	0.7 A
Light and function outputs – of which outside interface	6, summary current: max. 0.5 A 4
Max. decoder sum current	0.7 A
Short-circuit protection of all outputs	☒ Yes ☐ No
Dimensions	13 x 9 x 2.6 mm
RailCom®	☒ Yes ☐ No
Complies with ZIMO article	☒ Yes ☐ No MX617L
Updatable	☒ Yes ☐ No
Breaking section support	
Lenz ABC	☒ Yes ☐ No
Märklin 72441/72442	☒ Yes ☐ No
ZIMO HLU	☒ Yes ☐ No
Connection possibility for energy storage	☐ Yes ☒ No
Standard sound (Steam-, Diesel-, Electric locomotives)	☐ Yes ☒ No
Loudspeaker	☐ Yes ☒ No